Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (**Currently Amended**) A method of providing pattern recognition, said method comprising the steps of:

inputting a pattern;

transforming the input pattern to provide a set of at least one feature for a classifier which classifies into classes, wherein there is only one feature space transformation for all classes;

said transforming step comprising the step of minimizing the probability of subsequent misclassification of the at least one feature in the classifier; said minimizing step comprising:

developing an objective function, wherein said objective function maximizes an average pairwise divergence over all dimensions at a single step; and

optimizing the objective function through gradient decent, wherein all dimensions of a matrix are optimized via optimizing the objective function;

wherein the optimizing is carried out in an unconstrained manner over all possible matrices; and

wherein the objective function is initialized with an LDA matrix.

- 2. (Cancelled)
- 3. (Cancelled)
- 4. (**Original**) The method of Claim 1, further comprising the step of querying whether the optimized objective function converges.
- 5. (**Original**) The method according to Claim 4, further comprising the step of repeating said optimizing step if the optimized objective function does not converge.
- 6. (**Original**) The method according to Claim 1, wherein said pattern recognition is speech recognition.
- 7. (**Currently Amended**) An apparatus for providing pattern recognition, said apparatus comprising:

an input interface for inputting a pattern;

a transformer for transforming the input pattern to provide a set of at least one feature for a classifier which classifies into classes, wherein there is only one feature space transformation for all classes;

said transformer being adapted to minimize the probability of subsequent misclassification of the at least one feature in the classifier;

said transformer further being adapted to:

developing develop an objective function, wherein said objective function maximizes an average pairwise divergence over all dimensions at a single step; and

optimizing optimize the objective function through gradient decent,
wherein all dimensions of a matrix are optimized via optimizing the objective
function;

wherein the optimizing is carried out in an unconstrained manner over all possible matrices; and

wherein the objective function is initialized using an LDA matrix...

- 8. (Cancelled)
- 9. (Cancelled)
- 10. (**Original**) The apparatus according to Claim 7, wherein said transformer is further adapted to query whether the optimized objective function converges.
- 11. (**Original**) The apparatus according to Claim 10, wherein said transformer is further adapted to repeat optimization of the objective function if the optimized objective function does not converge.

- 12. (**Original**) The apparatus according to Claim7, wherein said pattern recognition is speech recognition.
- 13. (**Currently Amended**) A program storage device readable by machine, tangibly embodying a program of instructions executable by the machine to perform method steps for providing pattern recognition, said method comprising the steps of:

inputting a pattern;

transforming the input pattern to provide a set of at least one feature for a classifier which classifies into classes, wherein there is only one feature space transformation for all classes;

said transforming step comprising the step of minimizing the probability of subsequent misclassification of the at least one feature in the classifier; said minimizing step comprising:

developing an objective function, wherein said objective function maximizes an average pairwise divergence over all dimensions at a single step; and

optimizing the objective function through gradient decent, wherein all dimensions of a matrix are optimized via optimizing the objective function;

wherein the optimization is carried out in an unconstrained manner over all possible matrices; and

wherein the objective function is initialized with an LDA matrix.

- 14. (**Previously Presented**) The method according to claim 1, wherein said objective function is an average pairwise divergence related to the probability of misclassification of a projected space based on classes having uniform prior probabilities.
 - 15. (Cancelled)
 - 16. (Cancelled)
- 17. (**Previously Presented**) The method according to claim 1, wherein said objective function comprises means, covariances, and prior probabilities.
- 18. (**Previously Presented**) The method according to claim 1, wherein said objective function is expressed by the following equation:

$$D_{\theta} = \frac{1}{C(C-1)} trace \left\{ \sum_{i=1}^{C} (\theta \sum_{i} \theta^{T})^{-1} \theta S_{i} \theta^{T} \right\} - p$$

where
$$S_i = \sum_{i \neq i} \sum_j + (\mu_i - \mu_j) (\mu_i - \mu_j)^T$$
, $i = 1, ..., C$.